

# QM7500

Large Character Ink Jet Printer



**MSSE**

**QM7500** is a compact single line ink jet system that can be quickly installed, programmed and printing in minutes. The easy to use icon keys allow you to adjust and edit product codes with a single touch. Customize time and date codes, expiration dates, rollover hour and more. Menu driven programs include electronically accurate automatic date change, clock functions and consecutive counts. The QM7500 is a great low cost solution with its high ink mileage and low maintenance requirements.

NRP Technologies Pvt. Ltd.,

Registered Office: H.No. 12-6-2/186, Vivek Nagar | Kukatpally, Hyderabad - 500 072 |  
Andhra Pradesh  
Phone: +91 96765 95558 / 96768 95558 | nrp.technologies@gmail.com |

[www.nrptechnologies.com](http://www.nrptechnologies.com)



**The QM7500 kit includes:**  
the controller/key-pad, printhead,  
power pack, power cord, mounting  
brackets, self pressurized ink  
cartridges and solvent cartridge.



## QM7500 LARGE CHARACTER INK JET PRINTER

### SPECIFICATIONS:

#### System Includes

- Controller/Input Device
- Printhead
- Universal Power Supply
- Mounting Bracketry
- Starter Ink and Solvent Kit

#### Built-in software features

- Customized Time and Date Codes
- Julian Date
- Rollover Hour
- Expiration Date for automatic printing of up to two distinct dates of expiration
- Shift Organizer for automatic coding by particular shifts (up to 4 shifts)
- Print Delay for message placement
- Character Width adjustment
- Consecutive Incremental Numbering

#### Selectable Languages (Built-in)

- Dutch, English, Finnish, French, German, Italian, Portuguese, Spanish, Swedish, Hebrew, Cyrillic, Greek
- Special application units include: Arabic, Chinese
- All characters and accents unique to these languages are printable

#### Print heights

- Standard print height: 3/8" (10 mm)
- Optional heights: 5/16" (7 mm)
- 1/2" (15 mm)
- 3/4" (20mm)

#### Character Fonts

- 7x5 dot matrix, 54 printable ASCII characters
- Printable accented characters

#### Ink Consumption

- Average 120,000 characters per cartridge

#### Conveyer Line Speed

- 20 fpm (6.1 mpm) to 200 fpm (61.0 mpm)

#### Message Length

- Up to 40 characters

#### Message Storage Capacity

- Up to 52 messages

#### Operating Temperature Range

- 40°F (4°C) to 120°F (49°C)

#### Electrical

- System uses Universal Switching Power Supply

#### Ink System

- Internally Regulated Ink System
- Factory Set
- No Adjustment Necessary

#### Ink

- 8oz (.23 liter) bladder pressurized, non-aerosol ink bottles
- Applications, porous surfaces only

#### Shipping Weight

- 14lbs (6.4 kg)

#### Mounting Bracketry

- 15" (38.9 cm) and 9" (22.8) mounting tubes with 1" (2.54 cm) outside diameter (OD) includes 2 hand levers for simple Up/Down and In/Out adjustments.

#### Optional Bracketry For Special Installations

- Long Reach Bracket Kit available for special mounting situations
- Remote Bracket Assembly Kit enables printhead to be mounted up to 20' (6.1m) from controller



# MSSE